

The global leader in
door opening solutions

Rockwood K2060 - Plastic Kick Plate - Heavy Duty .060" Thick



Specifications:

MATERIAL:

.060" Kydex® 160 PVC Acrylic Alloy Plastic*

FASTENERS:

#6 x 3/4" Tapered Head Sheet Metal Screws

FEATURES:

- Push Side Plate Width - 2" less than door width
- Pull Side Plate Width - 1 1/2" less than door width

ORDERING:

Specify height x width x finish code. Add any options

OPTIONS:

- Cutouts for locks, louvers, or windows
- SA - self-adhesive mounting (K2060SA)
- SA-F - self-adhesive mounting (K2060SA-F) and UL approved for use of 90-minute wood doors and 3-hour metal doors

NFPA 80 STANDARDS - 2-4.5 Protection Plates: Factory-installed protection plates shall be installed in accordance with the listing of the door. Field-installed protection plates shall be labeled and installed in accordance with their listing.

Exception: Labeling is not required where the top of the protection plate is not more than 16 in. (406 mm) above the bottom of the door.

*Kydex 160 meets Class 1A building code ratings up to .060" thick

Available Finishes:

- Beige
- Calcutta Black
- Chocolate Brown
- Pewter Gray

WEIGHT:

8" x 34" = 1.0 lbs.

ANSI:

J105 - plastic armor
plate

J106 - plastic kick
plate

J107 - plastic stretcher
& mop plate